# **NJP Floor**

NJP Floor - 5744165138

The fixture provides direct glare-free horizontal light while reflecting some of the light through the rear of the head, illuminating the top of the arm. The ergonomic design of the fixture head shapes the light and gives optimal light direction. A simple mechanical system provides great freedom of movement, so the light can always be set in the ideal position in the workspace. The shade is painted white on the inside, reflecting comfortable diffused light.





### nendo

In 2002 Oki Sato founded nendo design studio. nendo means 'clay' in Japanese – or more specifically, modelling clay such as plasticine. A unique material that makes it easy to do creative modelling.





#### **NJP Floor**

### **Product info**

#### Information

Driver fitted externally on cord. The light has two built-in intensities. The weight includes the base plate. The innovation of the LED technology is constant. The specifications mentioned are based on present technology.

#### Mounting

Cord type: Black or white. Cord length: 1,7m. Switch: On the fixture head. Timer function: 4 hours or 8 hours. LED driver: separate, plugs into power outlet. The light has two built-in intensities.

#### Finish

White, black, light alu grey or dark alu grey, powder coated.

#### Materials

Base: Steel. Arms and lamp head: Aluminium. Joints: Anodised Aluminium. Stem: Aluminium.

#### Sizes and weights

Width x Height x Length (mm) | 260 x 1250 x 560 Max 7.2 kg

#### Class

Ingress protection IP20. Electric shock protection II.

#### Light source

LED 2700K 10W Lumen: 529

#### Information

Driver fitted externally on cord. The light has two built-in intensities. The weight includes the base plate. The innovation of the LED technology is constant. The specifications mentioned are based on present technology.

### **Product family**







NJP Table

NJP Wall


NJP Mini



NJP Wall Box



## Light distribution diagrams



### Spare parts & accessories

Product	Variant number
Adaptor 12V black	5744164867
Adaptor 12V white	5744164870
NJP bushing plast	5744165183

### **Data specifications**

Colour Black Length 560



#### NJP Floor

Width	260
Built-in Height	-
Class	II
Standby (W)	-
Inrush Current	-
Kelvin	2700
SDCM	3
Watt	10
Light control	-
UGR Transversal / Axial	19.3/19.3
Driver life	_

Height	1250
IP class	20
Net Weight	7.2
Power Factor (P = 100 % / P = 50 %)	0.53/0.46
Light source	LED 2700K 10W
CRI	97
Lumen	529
Efficacy	53
Min. Dim Level (%)	50
L80B50 (hours)	>100.000